SKYEYE-3DPC

3D People Counting Analysis System

We use innovative 3D stature identification and tracking technology, combined with unique 3D depth sensing applications, development out of the ultra-high accuracy of the people counter. Installed at the entrance above the ceiling, can be accurately recorded daily number of people entering and leaving. Daily return to the flow of information to the background management system, Web-based queries to manage passenger information on floors and entrances and exits. Users can plan according to a variety of time or regional needs report and analyze the chart to do the record, such as the occurrence of network connection disconnected, the system will immediately send e-mail prompt.



Product Benefits

- ✓ Statistics and analysis of passenger flow information of stores
- ✓ Can be combined with POS information analysis bag rate
- ✓ Analysis of the management of the store / store business performance
- ☑ Effective allocation of management of human resources


Product Characteristics


- ✓ Up to 30 fps tracking over 95% (inclusive) above accuracy.
- ☑ Can be used for no lighting, indoor environment.
- ✓ U-type rotation detection free counting.
- ▼ Real-time bidirectional counting.
- ▼ Filter carts and strollers.
- ✓ Real-time count data output.
- ✓ Instant pedestrian path tracking.
- ✓ Instant remote site view.





| System Components | Title | Details |
|-------------------------------|-------------------------------|---|
| | Mounting Types | Flush Mount, On-Ceiling Mount |
| | Image Sensor | 3D Depth Sensor |
| | 3D Frame Rate | 30fps |
| | Illumination | 0 Lux, Indoor application |
| | Detection FOV | 74° x 57° x 86° |
| | Mounting Height | 2.2m to 5m |
| | Installation Angle | +/-15° in x-axis and +/-5° in y-axis |
| | Detection Area | 2.1m x 1.65m to 6m x 4.5m |
| | Operating Temperature | 0 to 50 °C |
| | Dimension | 180mm (φ) x 68mm (W) / 48mm(H) |
| | Power Consumption | Max 12.95W, 802.3af PoE Class 3 |
| | Accuracy | over 95% (inclusive) above accuracy |
| | Enclosure | Aluminium |
| | Degree of Protection | IP30 |
| | Interface | PoE RJ45 |
| | LED Indicator | Status Indicator |
| Data statistics hardware host | Size | 190(L)×165(W)×43(H)mm |
| | CPU | Intel Celeron G3930 |
| | Memory | DDR4 2133 |
| | Storage | 128GB SSD |
| | Network | RJ45 Gigabit LAN port |
| Data statistics software | Web Server | According to half an hour, time, day, week, |
| Data statistics contware | statistical analysis software | month, year record analysis query |







ecaF Technology, Inc.